



PERFORMANCE SPECIFICATIONS

DC Energy	5kWh
Voltage Range	21.6Vdc to 30.4Vdc
DC Voltage (Nominal)	24Vdc
Internal Resistance	<4 mΩ

CELL SPECIFICATIONS

Technology	Encapsulated Cell
Nominal Cell Voltage	6.4~6.6Vdc / Cell (Encapsulated) 1/2 + 0.12V Envelope

CHARGE CHARACTERISTICS

Maximum Charge Current	1C (200A) maximum (maximum continuous charging current) @25°C
Charging Method	CC/CP/VP

DISCHARGE SPECIFICATIONS

Maximum Discharge Current	1.5C (300A) maximum (maximum continuous discharging current) @25°C
Discharging Method	CC/CP/VP

MECHANICAL SPECIFICATIONS

Dimensions (W x H x D) mm	430 x 154 x 590
Weight (kg)	60 kg
Module Casing Material	Aluminium oxide / GI Powdered
Terminal Type	300A Terminal Post

SMART FEATURES


Communication	WIFI / CANBUS / BLUETOOTH
Alarm	Buzzer alarm in the event of over/under-voltage, Over Current, Over Temperature



Front view



Side view



Top view

ENVIRONMENT SPECIFICATIONS

Cell Operating Temperature ¹	Charging: 0°C ~ 50°C (0°C to 10°C current limit 20A charge)
	Discharging: -20°C ~ +55°C
Operating Humidity	Non-Condensing
Storage Temperature	-10°C ~ +45°C (<3 months, SOC: 20% ~ 60%) -10°C ~ +35°C (<1 year, SOC: 30% ~ 60%)

MODULE SERVICE LIFE

Projected Cycle Life ^{3,4}	500,000 Cycles
Projected Calendar Life ⁵	25 Years
Shelf Life ⁶	10 Years
Warehousing	Can be stored at any SOC without affecting cycle life

PRECAUTIONS


Alarm	In case of alarm, immediately rectify/attend to the cause of the alarm
Physical Damage	In case the module is physically damaged due to an event, do not install and energize the module under any circumstances and contact your re-seller or after sales
Short Circuit	Ensure precautions to prevent short-circuit under all circumstances
Galvanic isolation	When connecting to external devices ensure that galvanic isolation does not exceed 1000V
Series Connection	All modules must be at 100% SOC before connecting in series. A maximum of 20 modules with Module combiner can be connected in series. Please contact your reseller / After sales support when connecting the module in series.
Parallel Connection	All modules must be at 100% SOC before connecting in series. There is no limit on the number of modules that can be connected in parallel.
Series - Parallel Connection	Modules cannot be connected in series - parallel combination under any circumstance.



Front view



Side view



Top view

¹The temperature range indicates the range in which the encapsulated cells can operate. The performance of the cells may vary if they are continuously operated outside a temperature range of -20°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in this spec sheet. The operating temperature range of the module varies based on the application. If the module is to be operated continuously outside a temperature range of -20°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in the spec sheet, please consult Enercap or its Reseller prior to deploying.

²Warranty conditions will apply. Please consult your, Reseller or Enercap for warranty conditions applicable to your region.

³Projected life of encapsulated cells. Cycle life will vary if cycled more than 4 times a day.

⁴Additional terms and conditions, including a limited warranty, will apply at the time of purchase.

⁵Projected Calendar life of encapsulated cells from the date of first operation.

⁶Shelf life is the life of the module (in years) from the date it is manufactured to the time it is first operated

Product dimensions are for reference only unless otherwise identified and may change without notice.

For critical applications, please contact your Reseller or After Sales support.